Reolink Go Series G440 Dome IP security camera Indoor & outdoor 3840 x 2160 pixels Wall

Brand : Reolink

Product code: 6975253983261

Product name : Go Series G440

Reolink Go Series G440. Type: IP security camera, Placement supported: Indoor & outdoor, Connectivity technology: Wireless. Mounting type: Wall, Product colour: White, Form factor: Dome. Lens viewing angle, horizontal: 90°, Lens viewing angle, vertical: 47°, Lens viewing angle, diagonal: 110°. Sensor type: CMOS, Optical sensor size: 25.4 / 2.7 mm (1 / 2.7"). Digital zoom: 16x

Performance	
Type *	IP security camera
Placement supported *	Indoor & outdoor
Connectivity technology *	Wireless
PTZ control	✓
Virtual assistant	Google Assistant
Built-in light	✓
Colour temperature	6500 K

Design	
Form factor *	Dome
Mounting type *	Wall
Product colour *	White
Protection features	Waterproof
International Protection (IP) code	IP64
Weatherproof	✓

Camera	
Lens viewing angle, horizontal	90°
Lens viewing angle, vertical	47°
Lens viewing angle, diagonal	110°
Tilt angle range	0 - 140°
Pan range	0 - 355°

Image sensor	
Number of sensors	1
Optical sensor size	25.4 / 2.7 mm (1 / 2.7")
Sensor type *	CMOS

Lens system	
Zoom capability	✓
Digital zoom	16x
Fixed focus	✓

Night vision	
Night vision *	✓
Night vision distance	10 m
LED type	IR
Number of illumination LEDs	2
Infra-red wavelength	850 nm

Video	
Maximum resolution *	3840 x 2160 pixels
Total megapixels *	8 MP
Video compression formats	H.265

Video	
Video recording	✓
Frame rate	15 fps

Audio	
Built-in speaker(s)	✓
Audio system	2-way
Built-in microphone	✓

Network	
Ethernet LAN *	✗
Wi-Fi *	✗
Bluetooth *	✗
Mobile network connection	✓
Mobile network generation	4G
4G standard	LTE-TDD & LTE-FDD
3G standards	HSPA+, UMTS, WCDMA

Storage	
Built-in HDD *	✗
Card reader integrated	✓
Compatible memory cards	MicroSD (TransFlash)
Maximum memory card size	128 GB

Ports & interfaces	
USB port	✓

Security	
Video motion detection	✓
Alert notification type	E-mail, Push notification
Intelligent Video Surveillance (IVS) system features	Human detection, Vehicle detection
Motion sensor	✓
Motion sensor technology	Passive infrared (PIR) sensor

Power	
Power source type *	Battery, Solar, USB
Battery capacity	6000 mAh
Rechargeable battery	✓

Operational conditions	
Operating temperature (T-T)	-10 - 55 °C

Weight & dimensions	
Height	122 mm
Diameter	9.8 cm
Weight	496 g

Packaging content	
Number of cameras *	1

6975253983261

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 03-MAY-2024. Prints or copies of Information are only valid on the printed Publication date